

# Product information **DATA SHEET**



## **FibroTech X-TRA FINE**

## **Fibrotech ´s unique benefits**

**FibroTech is the name behind our woodwool cement boards. FibroTech acoustic ceilings are simply made of cement and woodwool. We use the finest white cement from Aalborg Portland. This composition has many unique benefits, such as noise reduction, sound insulation, acoustic control and a healthy indoor climate. Furthermore, it has an effective fire protection. With FibroTech, the possibilities are many, as our acoustic panels are available with different edges and come in all dimensions and colors.**

### **Good acoustics**

Our woodwool cement boards adds excellent acoustics to a room – or different sections of it. When using acoustic panels from FibroTech, an acoustic control and attenuating reverberation is achieved. Therefore, our products are particularly suitable for interior ceilings with or without slopes, offices, all rooms and ceilings with hard floor coverings, larger entrances, covered terraces, sports halls, garages, stables, etc.

### **100% natural products**

Our woodwool cement boards are made from the natural products wood and cement, which combine building strength with natural properties. A facing of acoustic not only creates a comfortable sound environment. It also provides a better indoor climate.

### **Effective fire protection**

Our panels have fire-retardant properties, which are crucial for effective fire protection of structures. For example, a high melting point and a low smoke concentration are extremely important when evacuating people in buildings. All our products are CE marked and meet the fire requirements for fire class B / s1 / d0.

### **The product**

The FibroTech X-TRA FINE board definitely has the finest surface you can achieve for a beautiful acoustic ceiling. Our X-TRA FINE board is particularly suitable for the interior of ceilings, in all kinds of housing construction, offices, in large entrances and the like. Due to the nature of the material, color variations will occur.

### **Assembly and cleaning**

Before starting the assembly, we recommend reading our installation, storage and acclimatization instructions on [www.fibrotech.co.uk](http://www.fibrotech.co.uk).

It provides all the important information you need to get the best results. Improper storage and lack of acclimatization can cause the plates to change dimensions and weight.

FibroTech woodwool cement boards do not require more cleaning or care than other products. After installation, the boards can be cleaned with a vacuum cleaner or a wrung-out cloth.

Contact:  
TreeTops A/S  
DK-6580 Vamdrup  
Tel.: +45 70 266 233  
[info@treetops.dk](mailto:info@treetops.dk)  
[www.fibrotech.co.uk](http://www.fibrotech.co.uk)

DATA  
**MULTIFIN**

# Product information

# DATA SHEET



## FibroTech **X-TRA FINE** - 0,5 mm Woodwool - 5 mm bevel

DB/TUN 1950317

### **X-TRA FIN**

Dimension 600 x 1200 x 25 mm

**White RAL 9003**

m<sup>2</sup>: 0,72

Pcs./Pallet: 80

Weight: 11.7 kg/m<sup>2</sup>

DB/TUN 1838894

### **Screws**

Dimension 5,0 x 45 mm

Pieces pr. plate v/ 600 x 1200 mm

**White RAL 9003**

Torx 25

6 pcs.

Pcs./box.: 250

DB/TUN 1905470

### **Screws**

Dimension 5,0 x 45 mm

Pieces pr. plate v/ 600 x 1200 mm

**White RAL 9003**

Torx 25

6 pcs.

Pcs./box.: 100



## Properties

The table shows declaration in accordance with EN13168, which is the standard for woodwool cement.

TOLERANCES	
Length (mm)	+/- 2
Width (mm)	+/- 2
Thickness (mm)	+/- 2
Weight (%)	+/- 10
Perpendicularity (mm)	+/- 2
Flatness (mm)	+/- 3
HEAT	
Lambda-value W/m-K	0,072
FIRE	
Reaction to fire	B/s1/d0
SUBSTANCES	
Formaldehyde	E1
STANDARD	
Declared after	EN13168